

Material Safety Data Sheet



ANTISOIL 301

Section 1. Chemical product and company identification

Trade name : ANTISOIL 301
Product use : Cleaning product
Supplier : Ecolab Inc. Food & Beverage Division
370 N. Wabasha Street
St. Paul, MN 55102
1-800-392-3392
Code : 916080-02
Date of issue : 03-June-2009

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Hazards identification

Physical state : Liquid. [Liquid.]
Emergency overview : DANGER!

CAUSES DIGESTIVE TRACT, EYE AND SKIN BURNS.
CAUSES RESPIRATORY TRACT IRRITATION.
MAY BE HARMFUL IF SWALLOWED.
Can cause central nervous system (CNS) depression.

Do not ingest. Do not get in eyes, on skin or on clothing. Avoid breathing vapors, spray or mists. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Eyes : Corrosive to eyes.
Skin : Corrosive to the skin.
Inhalation : Severely irritating to the respiratory system. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.
Ingestion : Causes burns to mouth, throat and stomach. May be harmful if swallowed. Ingestion may cause nausea, weakness and central nervous system effects.

See toxicological information (section 11)

Section 3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>
TETRAPOTASSIUM PYROPHOSPHATE	7320-34-5	1 - 5
dipropylene glycol methyl ether	34590-94-8	1 - 5
PROPYLENE GLYCOL PROPYL ETHER	1569-01-3	1 - 5
METHOXYISOPROPANOL	107-98-2	1 - 5
poly(oxy-1,2-ethanediyl), .alpha.-phenyl-.omega.-hydroxy-, phosphate	39464-70-5	1 - 5
SODIUM METASILICATE	6834-92-0	1 - 5

Section 4. First aid measures

Eye contact : In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation : If inhaled, remove to fresh air. If exposed person is not breathing, give artificial respiration or oxygen applied by trained personnel. Get medical attention immediately.

Ingestion : If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire-fighting measures

Flash point : > 100°C

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
phosphorus oxides
metal oxide/oxides

Fire-fighting media and instructions : Use an extinguishing agent suitable for the surrounding fire.

Dike area of fire to prevent runoff.

In a fire or if heated, a pressure increase will occur and the container may burst.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions : Immediately contact emergency personnel. Stop leak if without risk. Use suitable protective equipment. Keep unnecessary personnel away. Do not touch or walk through spilled material.

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain it to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

Handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Storage : Keep out of reach of children. Keep container in a cool, well-ventilated area. Keep container tightly closed.
Do not store below the following temperature: -10°C

Section 8. Exposure controls/personal protection

Engineering measures : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Personal protection :

Eyes : Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.

Hands : Use chemical-resistant, impervious gloves.

Skin : Use synthetic apron, other protective equipment as necessary to prevent skin contact.

Respiratory : Wear appropriate respirator when ventilation is inadequate and occupational exposure limits are exceeded.

Name **Exposure limits**

dipropylene glycol methyl ether

ACGIH TLV (United States, 1/2008). Absorbed through skin.STEL: 909 mg/m³ 15 minute(s).

STEL: 150 ppm 15 minute(s).

TWA: 606 mg/m³ 8 hour(s).

TWA: 100 ppm 8 hour(s).

OSHA PEL (United States, 11/2006). Absorbed through skin.TWA: 600 mg/m³ 8 hour(s).

TWA: 100 ppm 8 hour(s).

NIOSH REL (United States, 6/2008). Absorbed through skin.

TWA: 100 ppm 10 hour(s).

TWA: 600 mg/m³ 10 hour(s).

STEL: 150 ppm 15 minute(s).

STEL: 900 mg/m³ 15 minute(s).

METHOXYISOPROPANOL

ACGIH TLV (United States, 1/2008).STEL: 553 mg/m³ 15 minute(s).

STEL: 150 ppm 15 minute(s).

TWA: 369 mg/m³ 8 hour(s).

TWA: 100 ppm 8 hour(s).

NIOSH REL (United States, 6/2008).

TWA: 100 ppm 10 hour(s).

TWA: 360 mg/m³ 10 hour(s).

STEL: 150 ppm 15 minute(s).

STEL: 540 mg/m³ 15 minute(s).

Section 9. Physical and chemical properties

Physical state	: Liquid. [Liquid.]
Color	: pink
Odor	: Faint odor.
pH	: 12.3 [Conc. (% w/w): 100%]
Relative density	: 1.079

Section 10. Stability and reactivity

Stability	: The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur.
Reactivity	: Highly reactive or incompatible with the following materials: acids.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Potential acute health effects

Eyes	: Corrosive to eyes.
Skin	: Corrosive to the skin.
Inhalation	: Severely irritating to the respiratory system. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness.
Ingestion	: Causes burns to mouth, throat and stomach. May be harmful if swallowed. Ingestion may cause nausea, weakness and central nervous system effects.

Potential chronic health effects

Target organs	: Contains material which may cause damage to the following organs: upper respiratory tract, central nervous system (CNS).
---------------	--

Section 12. Ecological information

Ecotoxicity data : Not available.

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN Classification

UN number	UN3266
Proper shipping name	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (potassium hydroxide, disodium metasilicate)
Class	8
Packing group	III

See shipping documents for specific transportation information.

Section 15. Regulatory information

HCS Classification : Corrosive material
Target organ effects

U.S. Federal regulations

TSCA 8(b) inventory : All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

California Prop. 65 : No products were found.

Section 16. Other information

Hazardous Material Information System (U.S.A.) :	Health	*	3
	Flammability		0
	Physical hazards		0

Date of issue : 03-June-2009.
Responsible name : Regulatory Affairs
Date of previous issue : 29-November-2006.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.