

**DIMENSIONS & WEIGHTS**

**GENERAL**

**CONNECTIONS**

	<b>EH020</b>	<b>EH030</b>	<b>EH040</b>	<b>EH055</b>
Capacity <i>lbs (kg)</i>	20 (8)	30 (12.6)	40 (17.3)	55 (22.8)
Cylinder Diameter <i>inch (mm)</i>	21.1 (536)	24.4 (620)	27.6 (700)	29.1 (739)
Cylinder Depth <i>inch (mm)</i>	13.8 (351)	16.4 (416)	17.7 (450)	21 (530)
Cylinder Volume <i>cu. ft (dm<sup>3</sup>)</i>	2.8 (79.2)	4.4 (126)	6.1 (173)	8.1 (228)
Net Weight <i>lbs. (kg)</i>	279 (127)	758 (344)	1049 (476)	1601 (726)
Crated Weight <i>lbs. (kg)</i>	301 (137)	820 (372)	1091 (495)	1687 (765)
Machine Width <i>inch (mm)</i>	27 (685)	31.3 (796)	34.2 (868)	39.4 (1000)
Machine Depth <i>inch (mm)</i>	27.6 (700)	34.9 (887)	37.9 (962)	48.8 (1240)
Machine Height <i>inch (mm)</i>	42.5 (1080)	52.2 (1325)	55.3 (1404)	57.9 (1470)
Door Opening <i>inch (mm)</i>	12.7 (322)	12.9 (327)	16.8 (426)	15.7 (400)
Floor to Door <i>inch (mm)</i>	15.4 (390)	20 (509)	20.3 (515)	21.1 (535)
Shipping Dimensions <i>inch (mm)</i> (WxDxH)	28.3 x 29.1 x 47.7 (720 x 740 x 1212)	32.4 x 37.2 x 58.5 (823 x 945 x 1485)	35.3 x 40 x 61.6 (897 x 1017 x 1565)	40.4 x 49.4 x 65 (1025 x 1255 x 1650)
Control Options	Logic	Logic or Intelligent	Logic or Intelligent	Intelligent
Washing Speeds <i>rpm</i>	Logic Control 50 Intelligent Control —	46.5 27/36/43/46.5	44 25/34/40/44	— 22/29/36/43
Spin Speeds <i>rpm</i>	50/100/580/690/780/970	46.5/100/400/600/800/1005	44/100/351/550/750/950	43/87/330/525/725/920
G-force	0.75/3/101/143/183/300	0.75/3/56/125/222/351	0.75/4/48/119/221/354	0.77/3.14/45/114/218/351
Modified Energy Factor (MEF)*	2.21	2.08	1.96	2.34
Water Consumption Factor (WCF)*	5.03	4.68	5.04	4.09
Drain Diameter <i>inch (mm)</i>	Pump Drain 1 (25.4) Gravity Drain 2 (51)	— 3 (80)	— 3 (80)	— 3 (80)
Water Inlets <i>inch (mm)</i>	3/4 (19)	3/4 (19)	3/4 (19)	3/4 (19)
Recommended Water Pressure <i>PSI (bar)</i>	30-60 (2-4)	30-60 (2-4)	30-60 (2-4)	30-60 (2-4)
Water Flow <i>gal/min (l/min)</i>	8 (30)	16 (60)	16 (60)	16 (60)
Steam Connection <i>inch (mm)</i>	—	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)
Steam Pressure (optional) <i>PSI (bar)</i>	—	29-87 (2-6)	29-87 (2-6)	29-87 (2-6)
Steam Flow (optional) <i>lbs/h (kg/h)</i>	—	176 (80)	176 (80)	176 (80)
Motor Power <i>kW</i>	0.8	0.87	1.3	1.75
Electric Heating Power <i>kW</i>	Single Phase 4.3 Three Phase —	8.4 —	10.6 —	— 20.3



\* Modified Energy Factor (MEF) measured in cubic feet per kilowatt-hour per cycle. Water Consumption Factor (WCF) measured in gallons per cycle per cylinder cubic feet. MEF and WCF statistics are according to Department of Energy (DOE) testing standards report by Intertek, an independent testing laboratory. The report for EH020, EH030 and EH040 is dated February 27, 2007 (report no. 3109575CRT-002). The report for EH055 is dated August 12, 2009 (report no. 3184405CRT-001a)

\*\* Product specifications are subject to change without notice. For the most current and complete technical specifications, architectural line drawings and warranty information, please visit [www.continentalgirbau.com](http://www.continentalgirbau.com).

**DISTRIBUTED BY:**



[www.continentalgirbau.com](http://www.continentalgirbau.com) • 800-256-1073  
2500 State Road 44 • Oshkosh, WI 54904 • 920-231-8222 • Fax 920-231-4666